

**SECTION 317
ASPHALT MILLING**

317.1 DESCRIPTION:

The work under this section shall consist of milling existing asphalt concrete pavement where shown on the Plans or requested by the Engineer.

317.2 CONSTRUCTION REQUIREMENTS:

Contractor is responsible for locating all milling hazards on and below the surface within the areas to be milled including areas requiring special milling. Special milling is not a separate pay item and shall be paid for as Asphalt Milling.

The milling cut depth shall be the depth indicated on the Plans plus or minus 1/8 inch. The milling machine shall have electronic grade controls. Contractor shall remove the milled material and sweep the roadway clean with a power pick-up broom to the satisfaction of the Engineer.

Asphalt pavement adjacent to manholes, valve boxes, small radius curbs and other fixed objects that produce confined area shall be removed with milling equipment specifically designed to operate in constricted areas. The equipment shall be capable of removing asphalt concrete of the specified thickness without damage to, or displacement of, the adjacent object(s).

The Contractor shall be responsible for continually checking the milling operation to determine that the proper depth of milling has been achieved, that the proper profile and cross slope are achieved, and that the surface texture is (a) free from longitudinal ridges, and (b) has a uniform pattern.

The Contractor shall immediately notify the Engineer when:

- The existing pavement thickness is found to be less than anticipated and breaking of the underlying material occurs.
- Delamination of underlying material occurs.

The work shall result in a clean milled surface to the specified depth for the area indicated by the construction documents including the areas immediately around and next to any individual hazard within the area to be milled. The edge of milled area shall form a straight clean cut line.

For milled surfaces on major streets (arterial and collector streets) that will be subject to traffic prior to overlay, a tack coat per Section 329 may when authorized by the Engineer be applied to the milled surface as a dust control measure. The tack coat shall be applied after sweeping and prior to allowing traffic on the milled surface. The tack coat application rate shall be half of the prescribed tack rate or contract amount or an alternate rate as prescribed by the Engineer. The Contractor shall be responsible for clean-up of any tack coat tracking that occurs.

317.3 MEASUREMENT AND PAYMENT:

Measurement for Asphalt Milling will be by the square yard and shall only include area milled to the required depth and cross-section.

Payment for Asphalt Milling at the contract unit price shall be full compensation for the work, complete-in-place, including all asphalt milling, milling around structures, removal and disposal of milled materials, and sweeping.

Engineer approved tack coat applied for dust control will be paid at the contract rate for tack coat. No additional payment for the application of dust control tack coat shall be made.

- End of Section -